


CompX
CHICAGO

# STOCK® LOCKS

Standard Locks for Special Needs

# STOCK LOCKS®

**Through your CompX Chicago distributor . . . a program to meet your lock requirements.**

CompX Chicago manufactures a wide variety of locks for residential, commercial and industrial use. We've been solving security problems since the need for metal cabinet locks brought about the founding of our company in 1920.

The locks shown in this catalog are particularly well-suited to serve the replacement market...as well as component manufacturers.

Our experience in serving this market has shown us the importance of product quality, competitive pricing, proper packaging and immediate service and delivery. Working through your CompX Chicago distributor, we offer a program that is committed to serving your needs.

## A complete selection of locks

- Door and drawer locks for virtually every application, every security requirement.
- Locking devices of every description for use in schools, institutional and commercial buildings.
- Key blanks and keying kits to complement each of our locks.

## Packaged for your convenience

- All hardware is individually packed in see-thru poly-bags for product protection and easy inspection.
- Poly-bags of like hardware are grouped in popular quantities and placed in handy cases.
- Case designed for convenience in storage and ease in handling.
- Cases are labeled for quick identification.

ALOA — ASSOCIATE MEMBER
NBMDA — North American Building Material Distribution Association — ASSOCIATE MEMBER
BHMA member — builders hardware manufacturers association
SHDA — Security Hardware Distributors Association — ASSOCIATE MEMBER




***A CUT ABOVE.***

*The proven Ace II® original tubular lock, with its all brass construction and assembly process, provides professional locksmiths and their customers with excellent security at value prices.*

# HOW CABINET LOCKS ARE USED

**DOOR APPLICATION**

Bolt or cam at side locks to frame.





**LEFT HAND** **RIGHT HAND**


At which edge of door hinges are located determines hand of door when facing door.

**SINGLE DRAWER APPLICATIONS**

Drawer mounted lock – Bolt or cam locks on frame.




Frame mounted lock – Cam locks on back of drawer front with hook cam engaging strike.




**LID APPLICATION**

Lock engages strike mounted on underside of lid.



**SLIDING (By-pass) DOOR APPLICATION**

Lock engages strike mounted on rear door.



CompX® CHICAGO

***Celebrating 90 years of service to the security industry.***

# The Family Of...

CompX®
SECURITY PRODUCTS

CompX®
NATIONAL

PO Box 200
Mauldin, SC 29662
Phone: 864-297-6655 Fax: 864-297-9987
E-Mail: national@compx.com
compx.com

CompX®
FORT

715 Center Street
Grayslake, IL 60030
Phone: 847-752-2500 Fax: 847-752-2419
E-Mail: fort@compx.com
compx.com


CompX®
TIMBERLINE

715 Center Street
Grayslake, IL 60030
Phone: 847-752-2600 Fax: 847.752.2420
E-Mail: timberline@compx.com
compx.com

CompX®
CHICAGO

PO Box 200
Mauldin, SC 29662
Phone: 864-297-6655 Fax: 864-297-9987
E-Mail: chicago@compx.com
compx.com

# ACE II® CAM TYPE UNIVERSAL FUNCTION LOCKS




***Conveniently Packaged! More Versatile Than Ever!***

- **Effective Retail Display**—packages include easy to follow instructions for replacement lock needs.
- **Convenient Field Use**—The Universal Function package includes everything you need for quick, easy installation.
- **All brass construction.**
- Ace II® assembly.
- Center plug contains anti-drill pin for added security.
- Polished Nickel finish.
- Furnished with straight locking cams which can be mounted vertically or horizontally and also a $^{1}/_{4}$" offset cam. Cams are $^{1}/_{8}$" thick X $^{3}/_{4}$" wide.
- Two keys per lock.
- D137-CLC key blank.

***Specifications:***


**KEY ROTATION/REMOVAL** is determined by the **STOP CAM** you select and how it is positioned.


A. 180° Clockwise Rotation - Key removal at 12 O'Clock.


B. 180° Counter Clockwise Rotation- Key removal at 12 O'Clock.


C. 90° Clockwise Rotation - Key removal at 12 & 3 O'Clock.

D. 90° Counter Clockwise Rotation - Key removal at 12 & 9 O'Clock.





| Lock No. | "B" Dim. | "C" Dim. | "D" Dim. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|---|
| C4198 | $1^{1}/_{8}$ 28.6mm | $^{23}/_{64}$ 9.04mm | $^{19}/_{32}$ 15.1mm | 6224 6225 7302 | 200 | 25 |
| C4153 | $1^{1}/_{8}$ 28.6mm | $^{1}/_{4}$ 6.4mm | $^{11}/_{16}$ 17.5mm | 6032 6234 7302 7525 PL-505 PL910 | 200 | 25 |
| C4152 | $1^{1}/_{8}$ 28.6mm | $^{13}/_{64}$ 5.2mm | $^{15}/_{16}$ 23.8mm | 7302 PL-505 PL910 | 200 | 25 |
| C4160 | $1^{1}/_{8}$ 28.6mm | $^{13}/_{64}$ 5.2mm | $1^{3}/_{32}$ 27.8mm | 6234 6502 7302 PL-505 | 200 | 25 |




STOCK LOCKS®

# SLIDING DOOR LOCKS


- Reliable ACE II® cylinder can be keyed compatibly with other ACE II® models
- Solid die cast housing and locking pin
- Retrofits most existing sliding door locks
- Easy cylinder removal for replacement or rekeying
- Available keyed alike, keyed different and keyed in groups
- Bright chrome finish
- Two keys per lock
- D137-CLC key blank



C5170


| Lock No. | KA Codes | KD | Box Quantity |
|---|---|---|---|
| C5170 | 6303 7302 | 200 | 10 |



C1770

- Five disc tumbler plug in 7/8" diameter
- Die cast barrel
- C1770 utilizes a spring bolt which locks by pushing the cylinder in and released by turning the key 90° from locked (12 O'Clock) to unlocked (3 O'Clock) position.
- Keypull in locked and unlocked positions
- Satin Chrome finish.
- Mounting plate is 5/64" X 7/8" X 2" with 1 1/2" between mounting hole centers
- Two keys per lock
- DK-5 key blank

**No. 1770**




| Lock No. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|
| C1770 | 1289 1454 | 200 | 10 |

# SAMPLE BOARDS


### ACE II TUBULAR LOCKS




### V69B-19 BOARD

V69B-19 Board displays Ace tubular cam locks, C4153 - C4198, C4235-DC switch lock, C4073 series switch locks, C5170 showcase lock, C4260-19 cylinder lock, C425519RL T-handle Cylinder, CSA4107 screw type lock.

### FILE LOCKS, SINGLE AND DOUBLE BITTED LOCKS




### V69B-20 BOARD

V69B-20 Board displays C5001LP, C5002LP & CEXP-19DC file cabinet locks, C1974 & C1975 bolt locks, C17256TNH six tumbler drawer lock, C3786 single bitted cam lock, C1770 single bitted sliding door lock, C1802 & C3186 double bitted cam locks, C2174 series & C3535BDC switch locks, C1968 drawer lock.

# SERVICE PARTS KITS

***Ace® Factory Original Parts now in Convenient Service Kits for Locksmiths!***

***Ace® Locking Cam and Tumbler Service Kits from CompX Chicago save invaluable time!***


They provide all the parts needed to service locks in one compact container. No more wasted trips back to the shop to find forgotten tumblers, springs… *it's all right at your fingertips.*

Single and Double Bitted Service Kits also available (see page 7). Contact your local distributor to order and save both time and money!





**Ace® Locking Cams Service Kit**


*Part No. D9629*





6-165
Quantity: 10





7-67
Quantity: 10





7-45
Quantity: 10





7-101
Quantity: 10





7-50
Quantity: 10





7-13
Quantity: 10





7-42
Quantity: 10





7-192
Quantity: 10





7-209
Quantity: 10





7-240
Quantity: 10




2374-NS
40291-901
Replaces 2374 & 1216-1
Quantity: 20



Quantity: 20



2059-44
Quantity: 10



29-17
Quantity: 20

*Note: Cams Dimensions are 3/4 wide by 1/4 thick.*





**Ace® Tumbler Service Kit**

*Part No. D9630*


Quantity: 200 pieces per compartment, unless otherwise marked




2913-T-1
42495




2913-T-2
42506




2913-T-3
42517




2913-T-4
42528



2913-T-5
42539



2913-T-6
42550



2913-T-7
42561




Tumbler Springs
2929-11M
42872




Tumbler Springs
2929-11M
42872




2913-B-1
42429




2913-B-3
42440



2913-B-5
42451



Assembly Pin
22-42-HY
20273




Depth Key
43010-420
Quantity: 1



All part numbers shown in green are available through the STOCK LOCKS program.

STOCK LOCKS®




**Single Bitted Service Kit -** *Part No. D9094*


Quantity: 100

#1 – 41043
#2 – 41050
#3 – 41065
#4 – 41076
#5 – 41087


Quantity: 100

#M13
41094


Quantity: 100


#M15
41096


Quantity: 100

#M31
41095


Quantity: 100

#M35
41091


Quantity: 100

#M51
41092


Quantity: 100

#M53
41093


Quantity: 300


Tumbler Spring
37646


Quantity: 50

Crescent Spring
37193


Quantity: 50

Crescent Ring
37512


Quantity: 10

Hex Nut
40174


Quantity: 10


Cam Nut
47753


Quantity: 10

Retaining Clip
22058




**Double Bitted Service Kit -** *Part No. D9095*



Tumbler Assemblies
Standard – 43445
Off Center
Left – 43446
Right – 43443
K4W – 43447
Quantity: 5 each



Double Bitted
Tumblers
41098
Quantity: 220



Tumbler Springs
40461
Quantity: 20



Keyblanks
K4S – 83001
K4L – 83002
K4R – 83003
Quantity: 10 each



K4W Keyblanks
83004
Quantity: 10



Flat Washer (3/4 I.D.)
41307
Quantity: 10




Lock Washer (1/2 I.D.)
27447
Quantity: 10



Crescent Spring
37193
Quantity: 50



Crescent Ring
37512
Quantity: 50



Hex Nut
40174
Quantity: 10



Cam Nut
47753
Quantity: 10



Retaining Clip
22058
Quantity: 10

### Replacement Parts for Service Kits

| Part No. | Description | Std. Pkg. |
|---|---|---|
| 6-165 | Ace Cam | 10 |
| 7-67 | Ace Cam | 10 |
| 7-45 | Ace Cam | 10 |
| 7-101 | Ace Cam | 10 |
| 7-13 | Ace Cam | 10 |
| 7-192 | Ace Cam | 10 |
| 7-209 | Ace Cam | 10 |
| 7-240 | Ace Cam | 10 |
| 7-50 | Ace Cam | 10 |
| 2059-44 | Mounting Washer | 25 |
| 29-17 | Cam Adaptor | 25 |

## GUIDE KEY SET

### *402 Cut Keys*

- Numbered from 2001 to 2576, but not in consecutive order. 2400 Series is not included.
- Order item #D9402.

### *KF Series Cut Keys*

- Cut Keys for KF series only.

## KEY CODE BOOK

### *Coding For CompX Chicago's Most Popular Keys.*


- Binder includes coding for the most frequently used single bitted, double bitted and pin tumbler keys.
- Order item #D9401.

# KEYLOC™ / STEELCASE® REPLACEMENT PLUGS




***KeyLOC™ – The tamper evident key ring from CompX Chicago.***

- Vinyl coated steel cables – the same used in the aircraft industry – resistant to cutting. If cut, cable is non-repairable.
- Cables are available in 3 sizes: 4", 6" and 9" loops. Key ring loops hold 10 to 50 keys.
- Retainer pins fit securely into ACE II® Cylinder nested in lightweight aluminum housing. Tampering of any kind is revealed immediately.
- Security ring clearly warns "DO NOT DUPLICATE."
- **Easy 1/4 turn cable installation.**
- All units supplied with 2 keys each. Includes security seal.
- Scratch resistant vinyl cover included.




| Lock No. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|
| C4201<br>4", 6" & 9" Cable Assembly | 6201 | 200 | 1 |
| C4201-4<br>4" Cable Assembly | 6201<br>6230<br>6255 | 200 | 5 |
| C4201-6<br>6" Cable Assembly | 6201<br>6230<br>6255 | 200 | 5 |
| C4201-9<br>9" Cable Assembly | 6201 | 200 | 1 |
| C4201-LC<br>Locking Cylinder only | 6201<br>6230<br>6248<br>6255 | 200 | 1 |
| 4201-5A | 4" cable only | | each |
| 4201-5B | 6" cable only | | each |
| 4201-5C | 9" cable only | | each |
| D137-CLC | ACE II® key blank | | 50 |

## STEELCASE® REPLACEMENT PLUGS



**Complete Plug Assembly**
*P1076-Series*



**Plug-Sub Assembly**
*CP1076-Series (Retaining Tumbler Only)*

***Take advantage of a tremendous replacement market. Millions of Steelcase desk locks are now in use!***

- **Retrofits in seconds** with the use of the removal tool.
- 6 disc tumbler construction easily rekeyable with Service Kit.
- Set up your own code systems for each customer with the CP-1076-90

| Lock No. | Description | Keyway | KD Changes | Box Quantity |
|---|---|---|---|---|
| P-1076 | Loaded Plug w/2 Keys | K101-K104<br>*(Specify Keyway K101-K104 or our choice)* | 150 | each |
| CP-1076-90 | Un-Loaded Plug<br>*(No Keys / Retainer Tumbler only)* | K101-K104 | | each |
| K-100 RK68 | Removal Tool | | | each |

Steelcase is a registered trademark of Steelcase, Inc., Grand Rapids, Michigan.



All part numbers shown in green are available through the STOCK LOCKS program.

STOCK LOCKS®

# "T" HANDLE ASSEMBLIES




OU-4260

*Handle and Cylinder dimensions do not conform to NAMA dimensional standards.*

***For Limited Spaces.***

- Accepts Ace II® cylinder No. 4260-19. See page 10.
- To use flat key cylinder No. P-1060-19, order "T" Handle No. OU-4260-6T.
- Available with 4260-19 or P-1060-19 cylinders only.
- Chrome finish.
- Customer must furnish "A" and "B" Dimension.





***New! 4200 Series.***
***Retrofits OU-4260 & OU-5560 "T" Handles.***

- Increased security for limited spaces.
- Accepts standard & long cylinder locks which meet NAMA dimensional standards.
- Available in $^{1}/_{4}$ turn, clockwise or counter-clockwise.
- Locking cams can be manufactured per customer requirement, **cam not included**.
- Available 90⁰ or 180⁰ rotation.
- Chrome textured finish for scratch resistance.
- Black finish available. Minimum order may apply.



OU-4200-NA




## STANDARD SCREW TYPE




OU-4265-NA

***All "T" Handles with suffix NA will accept cylinders which meet NAMA dimensional standards.***

***Easily Tighten Door Without Losing Seal.***

- When fully extended, handle is free wheeling to 360⁰.
  When partially depressed, handle is free wheeling to 120⁰.
- Furnished with $^{1}/_{2}$ x 13 threaded stud.
- Front design has built up flange and tapered "T" Handle construction.
- Accepts standard & long cylinders which meet NAMA dimensional standards.
- Chrome textured finish for scratch resistance.
- Customer must specify "A" Dimension.
- Minimum order may apply for non-standard stud lengths.
- Optional stainless steel handle available.




***NOTE:***
***When ordering T-Handles specify all information for proper stud.***


# “T” HANDLE CYLINDER LOCKS


## CYLINDER LOCKS




C425519RL


- 7 Pin tumbler.
- Brass locking bolt.
- Set screw hole for anti-pull feature when used in “T” Handle with set screw feature.
- Chrome finish.
- Thousands of combinations available.
- Two keys per lock.
- **Meets NAMA dimensional standards.**
- Available keyed alike, keyed different, keyed in groups.
- For application options, see page 9.
- D137-CLC key blank




- For use in OU-4260 “T” Handle only. See page 9.
- 7 pin tumbler.
- Brass locking pin.
- Chrome finish.
- Thousands of key combinations available.
- Two keys per lock.
- Available keyed alike, keyed different & keyed in groups.
- D137-CLC key blank







C4260-19


| Lock No. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|
| C425519RL | SP802 SP803 SP804 L463 | 200 | 10 |
| C4260-19 | L463 | 200 | 10 |



P-1060-19


- For use in OU-4260-6T “T” Handle only. See page 9.
- 6 disc tumblers.
- Over 200 key combinations available.
- Two keys per lock.
- Master keying available at additional cost.
- DK-101-H key blank.




# DOUBLE & SINGLE BITTED CAM LOCKS

## DOUBLE BITTED




C3186

- Eleven criss-cross blade tumbler plug in 3/4" diameter.
- Die cast barrel with two flats — 5/8" across.
- Key and cam rotation 90° from locked (12 O'Clock) to unlocked (3 O'Clock) position with keypull in locked position only.
- Straight cam furnished is 1/8" thick X 3/4" wide.
- Polish Nickel finish.
- Two keys per lock.
- Not available MK.
- DK-45 key blank.




C3186 & C3205

| Lock No. | "A" Dim. | "B" Dim. | "H" Dim. | "T" Dim. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|---|---|
| C3205 | 7/16" | 1 1/8" | 13/64" | 15/64" | 2001 2007 | 200 | 25 |
| C3186 | 5/8" | 1 1/8" | 5/32" | 13/32" | 2001 2007 | 200 | 25 |
| C1801 | 13/16" | 1 1/8" | 13/64" | 11/16" | 2001 | — | 25 |
| C1802 | 1 1/16" | 1 1/8" | 13/64" | 15/16" | 2001 2007 | — | 25 |
| 1803<br>DK-4 keyway only | 1 3/16" | 1 1/8" | 13/64" | 17/64" | 2141 | 200 | each |
| C1804 | 1 1/2" | 1 1/8" | 13/64" | 1 13/32" | 2001 | — | 25 |





1800 SERIES


## SINGLE BITTED



- Five disc tumbler plug in 3/4" diameter.
- Die cast barrel with two flats — 5/8" across.
- Key and cam rotation 90° from locked (12 O'Clock) to unlocked (3 O'Clock) position with keypull in locked position only.
- Straight cam furnished is 1/8" thick X 3/4" wide.
- Polish Nickel finish.
- Two keys per lock.
- Available in six disc tumbler.
- DK-5 key blank.





C3786




Recommended
Mounting Hole

| Lock No. | "A" Dim. | "B" Dim. | "H" Dim. | "T" Dim. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|---|---|
| 3705 | 7/16" | 1 1/8" | 1/4" | 13/64" | 1289 1454 | 200 | each |
| C3786 | 5/8" | 1 1/8" | 13/64" | 13/32" | 1289 1454 | 200 | 25 |
| C1701 | 13/16" | 1 1/8" | 13/64" | 11/16" | 1289 1454 | 200 | 25 |
| C1702 | 1 1/16" | 1 1/8" | 13/64" | 15/16" | 1454 | 200 | 25 |
| C1703 | 1 3/16" | 1 1/8" | 13/64" | 17/64" | 1289 1454 | 200 | 25 |
| C1704 | 1 1/2" | 1 1/8" | 13/64" | 1 13/32" | 1289 1454 | 200 | 25 |





1700 SERIES

**All part numbers shown in green are available through the STOCK LOCKS program.**


CompX CHICAGO

# CompX Chicago KEYBLANKS

***Genuine CompX Chicago key blanks are packed 50 per box.***
***Order in multiples of 50.***





| DK-4-L | DK-4 | DK-4-R | DK-4-W | DK-2-W | DK-2 | DK-18 |
|---|---|---|---|---|---|---|
| Off Center Left | Center Groove | Off Center Right | “W” Milling | “W” Milling | Center Groove | Thicker Blank |




| DK-103-G | DK-501 | DK-502 | DK-503 | DK-504 | DK-5 | DK-9 | DK-35 |
|---|---|---|---|---|---|---|---|
| 6-Tumbler | 5-Tumbler | 5-Tumbler | 5-Tumbler | 5-Tumbler | 5-Tumbler | 5-Tumbler | 5-Tumbler |





| DK-35-M | DK-38 | DK-39 | DK-P-1 | DK-P-2 | DK-P-3 | DK-P-9 |
|---|---|---|---|---|---|---|
| 5-Tumbler | 5-Tumbler | 5-Tumbler | 4-Pin Tumbler | 4-Pin Tumbler | 4-Pin Tumbler | 4-Pin Tumbler |




ACE® & ACE II®
Keyblank
D137-CLC

**GENUINE CHICAGO LOCK CO. KEY BLANKS DESIGNED FOR STEELCASE EQUIPMENT LOCKS.**




| DK-101-H | DK-102-H | DK-103-H | DK-104-H | DK-100-MH |
|---|---|---|---|---|
| 6-Tumbler | 6-Tumbler | 6-Tumbler | 6-Tumbler | 6-Tumbler |

*Steelcase is a registered trademark of Steelcase, Inc., Grand Rapids, Michigan.*



STOCK LOCKS®


## 40MM PADLOCKS / 50MM PADLOCKS





RC-4841 RC-4842

| Lock No. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|
| RC-4841 | PL505 7302 | 200 | 5 |
| RC-4842 | PL505 7302 | 200 | 5 |

### 40mm Padlock




### 50mm Padlock





*Dimensions shown are without vinyl covers*

### *Our Finest Security Padlock.*

- Two sizes available: 40mm and 50mm.
- Removable core and shackle.
- Extruded brass body.
- Hardened steel shackles to resist cutting and sawing.
- ACE II® 7 pin tubular lock with 2 keys.
- Self locking
- Scratch resistant vinyl cover.
- Frequent lubrication is recommended.
- D137-CLC key blank.

### *How to remove/reinstall cylinder and shackle.*





*Tools Needed: 5/64 and 3/32 Hex Wrenches.*

**How To Remove Cylinder**

1. Unlock padlock. Leave key in open position.
2. Move shackle away from the case.
3. Insert the 3/32 hex wrench into the shackle hole. Remove set screw (M5 x .8).
4. Insert the 5/64 hex wrench into the hole on the side of the case. Remove cylinder retaining screw (M4 x .7).
5. Hold key and gently pull cylinder out of case. (Save the loose stop washer for reassembly).

**How To Reinstall Cylinder**

1. Attach stop washer to the end of the lock cylinder.
2. Slide cylinder all the way down into padlock case.
3. Insert cylinder retaining screw (M4 x .7) into side of case. Tighten firmly with 5/64 hex wrench.
4. Insert set screw (M5 x .8) into shackle hole. Tighten firmly with 3/32 hex wrench.




*Tool Needed: 5/64 Hex Wrench.*

**How To Remove Shackle**

1. Unlock padlock and remove key.
2. Move shackle away from the case.
3. Insert the 5/64 hex wrench into the hole in the front of the case. Remove set screw (M4 x .7) and the shackle retaining pin.
4. Remove the shackle from the padlock. (Save the loose shackle spring for reassembly).

**How To Reinstall Shackle**

1. Be sure that shackle spring is in the shackle hole.
2. Insert new shackle and lock the padlock.
3. Insert retaining pin and set screw (M4 x .7) into the hole on front of the case. Tighten firmly with 5/64 hex wrench.


## ACE II® SEVEN PIN TUMBLER SCREW TYPE




CSA4107

- Ace II® lock assembly in 3/4" diameter.
- Barrel with two flats — 5/8" across.
- 360° key rotation with keypull every 180° (12 and 6 O'Clock).
- Two keys per lock.
- Includes body nut.
- Additional stud lengths available to special order. Minimum order and extended lead time may apply.
- D137-CLC key blank.

| Lock No. | "A" Dim. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|
| CSA4107 | 7 1/32" | 7341 | 200 | 10 |





## BOLT TYPE




C1968

- Five disc tumbler.
- Removable plug feature.
- Steel locking bolt.
- Two keys per lock.
- DK-5 key blank.




C1974


| Lock No. | "A" Dim. | "D" Dim. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|
| C1968 | 57/64" 22.6mm | 1 5/32" 29.6mm | 1289 1454 | 200 | 25 |
| C1974 | 19/32" 15.1mm | 27/32" 21.4mm | 1289 1454 | 200 | 25 |
| C1975 | 21/32" 16.7mm | 57/64" 22.6mm | 1289 1454 | 200 | 25 |





RECOMMENDED MOUNTING HOLE





1968
Standard finish
Brushed Brass




1975
Standard Finish
Satin Chrome





1974
Standard Finish
Satin Chrome




# SWITCH LOCKS

## SINGLE POLE, SINGLE THROW




C4073 SERIES




***Ace II® Lock Assembly.***

- Maintaining contact switch operated by manually rotating inserted key 90° clockwise from open to closed position.
- Momentary contact switch locks feature spring return from closed to open position after 90° clockwise key rotation to closed position.
- Contact configuration: SPST
- 7 amps @ 28 VAC/VDC
- Electrical Life: 6,000 cycles @ Max. Load.
- Contact Resistance: 50 milli ohms initial maximum.
- Bright Chrome finish.
- Two keys per lock.
- Master - Keying not available.
- D137-CLC key blank.


| Lock No. | Keypull | Contact | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|
| C4073-1DC | OFF Only | Maintaining | PL927 | 200 | 10 |
| C4073-2DC | OFF & ON | Maintaining | PL910 | 200 | 10 |
| C4073-70DC | OFF Only | Momentary | PL927 | 200 | 10 |

Warning: Improper connection to circuitry may result in shock. Since CompX Chicago does not control the use of its products, external wiring, switch lock selection, and/or use is not the responsibility of CompX Security Products.

## SINGLE POLE, SINGLE THROW




C2174 SERIES




***Double Bitted Assembly With Eleven Criss-Cross Blade Tumblers.***

- Lock operation same as 4073 Series.
- Contact configuration: SPST
- 7 amps @ 28 VAC/VDC
- Electrical Life: 6,000 cycles @ Max. Load.
- Contact Resistance: 50 milli ohms initial maximum.
- Bright Chrome Finish.
- Two keys per lock.
- Master - Keying not available.
- DK-4 key blank.

| Lock No. | Keypull | Contact | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|
| C2174-1DC | OFF Only | Maintaining | 2001 2007 | 200 | 10 |
| C2174-2DC | OFF & ON | Maintaining | 2001 2007 2387 | 200 | 10 |
| C2174-70DC | OFF Only | Momentary | 2001 2007 2126 | 200 | 10 |

Warning: Improper connection to circuitry may result in shock. Since CompX Chicago does not control the use of its products, external wiring, switch lock selection, and/or use is not the responsibility of CompX Security Products.

# SWITCH LOCKS

## SINGLE POLE, DOUBLE THROW

***4235 Series:***
***Ace II® Lock Assembly.***

***3535 Series:***
***Double Bitted Assembly With Eleven Criss-Cross Blade Tumblers.***




C4235 SERIES





C3535 SERIES

These features apply to both switch locks:


- 7 amps resistive/4 amps inductive @ 115 VAC or 28 VDC.
- Reliable snap action switch provides many thousands of electrical contacts without failure.
- Terminals designed to accept "AMP" .058 pin receptacles.
- Bright Chrome finish.
- Furnished with 10 inch, 20 gage stranded wire.
- Two keys per lock.
- Master - Keying not available.
- Maintaining only.
- **Switches are U.L. recognized & CSA listed.**
- D137-CLC key blank for tubular.
- DK-4 key blank for double bit lock.

*Contact factory for additional specifications.*




**Ace II® Switch Locks — SPDT**

| Lock No. | Keypull | Rotation | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|
| C4235-DC | 2 positions | 180° CW | CLC705 | 200 | 10 |
| 4235BDC | 1 position | 165° CW | CLC706 | 200 | each |




**Double Bitted Switch Locks — SPDT**

| Lock No. | Keypull | Rotation | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|
| 3535DDC | 2 positions | 180° CW | 2387 | 200 | each |
| C3535-BDC | 1 position | 165° CW | 2382 | 200 | 10 |

Warning: Improper connection to circuitry may result in shock. Since CompX Chicago does not control the use of its products, external wiring, switch lock selection, and/or use is not the responsibility of CompX Security Products.


# KEY HOLDER / SPECIAL PURPOSE LOCKS

## DRAWER & DOOR

- Six disc tumbler plug in $^{3}/_{4}$" diameter.
- Die cast barrel with two flats — $^{21}/_{32}$" across.
- Key and cam rotation 90° from locked (12 O'Clock) to unlocked (3 O'Clock) position with keypull in both positions.
- This lock designed to be used with customer's latching mechanism.
- Satin Nickel finish.
- Two keys per lock.
- DK-101-H key blank.




C17256TNH




| Lock No. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|
| C17256TNH | 1101X | 150 | 25 |


## FILING CABINET




CEXP-19DC

DK-P-2 key blank


- Four pin tumbler plug.
- Die cast barrel with die cast bolt.
- 5002LP has rectangular bolt.
- Other models have round bolt.
- Satin Chrome finish.
- Two keys per lock.





5001-LP



C5001LP
DK-P-1 key blank




5002-LP
DK-P-1 key blank




EXP-19DC

| Lock No. | "A" Dim. | "Bolt" Dim. | "D" Dim. | "O.A." Dim. | "W" Dim. | KA Codes | KD Changes | Box Quantity |
|---|---|---|---|---|---|---|---|---|
| C5001LP | $^{55}/_{64}$" | $^{9}/_{32}$"dia. | $^{5}/_{16}$" | $1^{3}/_{4}$" | $^{5}/_{32}$" | 1X03 3X5<br>1X04 2X01<br>1X20 2X02 | 200 | 10 |
| C5002LP* | $1^{7}/_{64}$" | $^{27}/_{64}$"x$^{9}/_{64}$" | $^{5}/_{16}$" | 2" | $^{5}/_{32}$" | | 200 | 10 |
| CEXP-19DC | $^{7}/_{8}$" | $^{1}/_{4}$"dia. | NA | $1^{33}/_{64}$" | NA | 5X75 | 200 | 10 |

* ***To order replacement locks for Steelcase equipment, specify 5002LP, KA# CL-S100.***

*Steelcase is a registered trademark of Steelcase, Inc., Grand Rapids, Michigan.*

**NOTES:**

# ACE KEY COVERS / WEATHER COVERS

### ACE® KEY COVERS





***Available in a large range of colors, these user friendly Ace II® Key Handle Covers from CompX Chicago make key management easy.***

Key Handle Covers are made of a durable, strong plastic that press-fit any ACE II® key. The larger size allows for better grip and overall control of the key.

Product No. Specified By Color (*Sold in packages of five.)*
**Available in the following colors:**

| | | | | |
|---|---|---|---|---|
| Light Blue<br>D9645 | Purple<br>D9651 | Yellow<br>D9646 | Tan<br>D9652 | Blue<br>D9650 |
| Green<br>D9648 | Brown<br>D9654 | White<br>D9649 | Orange<br>D9647 | Rust<br>D9653 |

### WEATHER COVERS




Dust Cap No. D9655-WC (Sold in packages of five.)

***Protect Switch Locks and Cam Locks from the elements with this economical, easy to install weather cover.***


Quality construction includes:

- Chrome plated zinc die cast cover.
- Stainless Steel mounting ring.
- Permanently installed rubber seal.
- Positive spring closure to ensure seal integrity.
- Inside dimension: .755"

Competitively priced, and in stock for immediate shipment.




# SPECIALTY STRIKE




| Lock No. | Description | Box Quantity |
|---|---|---|
| C500SP | Designed to lock file and box drawers when no other locking points are available. | 25 |




CompX CHICAGO

CompX SECURITY PRODUCTS

**MAIN OFFICE - FACTORY**
REGISTERED TO ISO 9001
CERTIFICATE NO. 10000456

PO Box 200
Mauldin, SC 29662
PH: 864-297-6655
FAX: 864-297-9987
compx.com

**WESTERN DISTRIBUTION CENTER**
9370 Buffalo Avenue, Unit 104
Rancho Cucamonga, CA 91730
PH: 909-476-7933
FAX: 909-476-8553

UL REGISTERED FIRM

Reorder #: F2644-002
October 2011
Printed in U.S.A.

COMPX NATIONAL
REGISTERED TO ISO 9001
CERTIFICATE NO. 10000456